

# MORE THAN AN OIL CHANGE



Keep your motorcycle operating at peak performance with H-D® Authorized Service. We know best how to service your bike with factory-approved methods and equipment assuring you of thorough and competent workmanship. Our regular maintenance always includes a comprehensive performance and safety inspection along with so much more. Why risk anything less?

- 1 Replace engine oil, filter, and drain plug O-ring. Torque drain plug to proper specification. Ensure proper oil level at operating temperature.
- 2 Check operation of all electrical equipment, lighting, and controls.
- 3 Inspect front and rear tire tread depth and air pressure. Check tightness of all spokes (if equipped).
- 4 Inspect fluid level and moisture content of front brake reservoir. Check torque of cover screws.
- 5 Check torque of switch housing screws, clutch lever handlebar clamp screws, and master cylinder handlebar screws.
- 6 Check engine coolant freeze point and inspect for leaks. Clean radiators or oil cooler.
- 7 Drain and replace primary chaincase lubricant and drain plug O-ring. (if applicable)
- 8 Drain and replace transmission lubricant and drain plug O-ring. (if applicable)
- 9 Inspect oil, brake, and fuel lines and fittings for leaks, contact, or abrasions.
- 10 Inspect rear brake reservoir for proper fluid level and moisture content. Check torque of cover screws.
- 11 Inspect front brake pads and discs. Ensure pad thickness is within specification.
- 12 Inspect rear brake pads and discs. Ensure pad thickness is within specification.
- 13 Check torque of front and rear axle nut.
- 14 Inspect and lubricate jiffy stand.
- 15 Lubricate clutch cable. Ensure proper cable adjustment and hand lever free play.
- 16 Check, adjust, and lubricate brake and clutch controls.
- 17 Inspect and adjust drive belt or chain. Inspect wheel sprocket.
- 18 Inspect exhaust system for leaks, cracks, and loose or missing fasteners or exhaust shields.
- 19 Check battery, clean connections and torque terminal screws.
- 20 Lubricate the fuel door, hinge, and latch.
- 21 Check for open recalls, product campaigns, trouble codes, and software updates.
- 22 Flush brake and clutch systems and replace DOT 4 brake and clutch fluids every two years.
- 23 Road test – verify component and system functions.

**SCHEDULE YOUR NEXT APPOINTMENT TODAY**



Depicted are areas serviced during the recommended 1000 mile service for 2024 Touring Models. Refer to owner's for more details.

©2024 H-D or its affiliates. H-D, Harley, Harley-Davidson and the Bar & Shield logo are among the trademarks of Harley-Davidson Motor Company.